



Perfect cleansing by 360° ultrasound



42 kHz frequency at 20 watt



Easy handling by simple touch on sensor button



67x67x39 mm 2.64x2.64x1.54" stainless steel tub



Rechargeable by USB-C standard



USB Type-C[®]

USB Type-C[®] input for recharge



Environment-friendly packaging



All features controlled by microprocessor



Highest product quality with 2 year warranty




Energy-efficient, gentle and absolutely safe

PRODUCT DESCRIPTION

The u-sonic 3 is an electronic rechargeable ultrasonic cleansing station. It cleanses and care all kind of ultrasonic cleanable parts within minutes by powerful ultrasound.

IDENTIFICATION

Product name: u-sonic 3
REF: 60400000
WEEE-Reg. no.: DE 47525015

 flow-med GmbH
Weinbergweg 10
73773 Aichwald
Germany

TECHNICAL DATA

Cleansing: Efficient cleansing by powerful ultrasound frequency at about 42 kHz
Sensor button: 1x touch for 4 minutes short cleansing, 2x touch for 8 minutes intensive cleansing
Touch and hold for 3 seconds for manual switch-off
Switch-off: Automatic after cycle end
Tub: Stainless steel tub, 125 ml max. water mark, inner dimension 67 x 67 x 39 mm (2.64 x 2.64 x 1.54")
Classes: Medical Device Class I, Protection class IP43, Appliance class II
Operation: 5V USB-C base with integrated LiPo battery and USB cable
Short time operation: 12 minutes
Safety: Input voltage monitoring at < 4 V and > 6 V
Automatic safety shutdown at temperatures > 100°C (212°F)
LiPo battery: Lithium-polymer, model 955465, 3.7V, 5,000 mAh, 18.5Wh, UN3481, charging time approx. 3 hours
Capacity: up to 7 short cycles or up to 3 intensive cycles
Power consumption: Maximum power 20 W, Stand-by power < 250 mW

PACKAGING CONTENT

u-sonic 3
USB-C cable (USB-A to USB-C) 1.0 m
Cleaning cloth
Instruction for use

ENERGY SUPPLY

No USB power supply included.
The LiPo battery can be recharged at any USB output or USB power supply (5V / 2A, DC)

WARRANTY

2 Years from production date **LOT**

MARKING



DIMENSIONS, WEIGHT AND UDI-DI

Unit:	100 mm x 100 mm x 78 mm (L x W x H)	450 g	UDI-DI
1 pcs product carton:	123 mm x 107 mm x 91 mm (L x W x H)	558 g	4260277011574
2 pcs shipping carton:	260 mm x 120 mm x 115 mm (L x W x H)	1.200 g	4260277011581
10 pcs shipping carton:	620 mm x 280 mm x 145 mm (L x W x H)	6.430 g	4260277011598