



Fast drying by efficient air flow blower



Hygienic cleansing by UV-C light for your health



Health improving blue light



Easy handling by simple touch on tactile buttons



Drying, cleansing and charging by Dual-USB standard



Gravity sensor for safety shut-off



Automatic turn-off after 2 hours



All features controlled by microprocessor



Highest product quality with 2 year warranty




Energy-efficient, gentle and absolutely safe

## PRODUCT DESCRIPTION

The dry-cap uv 2.1® is an electronic drying cap with USB-C connection and UV-C light for hygienic cleansing. It dries and cares for all types of rechargeable hearing aids, RIC receivers, tinnitus masks, ear moulds and hearing protection. Many other products can be hygienically cleansed too.

### IDENTIFICATION

Product name: dry-cap uv 2.1®  
REF: 90700000  
WEEE-Reg. no.: DE 47525015

 flow-med GmbH  
Weinbergweg 10  
73773 Aichwald  
Germany

### TECHNICAL DATA

**Drying:** Fast drying due to efficient air blower, no thermal stress  
High-performance fan 7.000 U/min, Airflow 2,56 CFM, Air press. 2,47 mm H2O, low noise 38 dB (A)

**Button:** Left button for Dry&Clean mode: 2 min. UV-C light + 116 min. drying + 2 min. UV-C light  
Right button for Clean Mode: Cleansing by 2 min. UV-C light

**Switch-off:** Automatic after 2 h / 2 min.

**Cleansing:** By UV-C light with 253.7 nm wavelength  
Up to 99.9% of all common germs and bacteria are effectively eliminated  
UV-C intensity max. 4,900 µW/cm², coverage area at 10 cm ~1,200 µW/cm²

**Operation:** 5V USB base via supplied Dual-USB switching power supply or USB 2.0 interface

**Safety:** Input voltage monitoring at < 4 V and > 6 V  
Automatic safety shutdown on movement by 3G sensor

**Power consumption:** Average power 1 W, Maximum power (UV-C) 3 W  
Stand-by power < 0.1 W

### PACKAGING CONTENT

dry-cap uv 2.1®  
Dual-USB power supply  
USB-A to USB-C cable 1.0 m  
Cleaning cloth  
Instruction for use

### ENERGY SUPPLY

Electronic Dual-USB switching power supply (class VI)  
Input: 100-240 V, AC 50/60 Hz  
Output: 5V, 2A, DC  
Type: EU / UK / US / JP / AUS available

### WARRANTY

2 Years from production date **LOT**

### LABEL



### DIMENSIONS, WEIGHT AND UDI-DI

Unit:	120 mm x 120 mm x 120 mm (L x W x H)	315 g	UDI-DI
1 Unit carton:	130 mm x 130 mm x 130 mm (L x W x H)	441 g	4260277010416
10 Unit carton:	675 mm x 275 mm x 153 mm (L x W x H)	5.100 g	4260277010423
20 Unit carton:	695 mm x 295 mm x 342 mm (L x W x H)	6.000 g	4260277010430