



## Product Name: Lacquer L nano

REF: 37511, 37512, 375130

Date of print: 20.04.2021 Date of last alteration: 20.04.2021



egger

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

egger Lacquer L nano  
UFI: KF2W-794W-M003-7A16

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### Use of the substance/mixture

Silicone based lacquer for use in audiology.

#### 1.3. Details of the supplier of the safety data sheet

Manufacturer/distributor: egger Otoplastik+Labortechnik GmbH  
Street/POB-No.: Aybühlweg 59  
Postal code/city/country: 87439 Kempten/Germany  
Telephone: +49 831 58113-60  
Telefax: +49 831 58113-14  
Internet: www.egger.online  
E-mail: sales@egger.online

#### 1.4. Emergency telephone number: +49 89 19240

Emergency number: Munich, Germany, toxicological dep. of the II. Med. Hospital)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Regulation (EC) No. 1272/2008

Hazard categories:

Flammable liquid: Flam. Liq. 2

Acute toxicity: Acute Tox. 4

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Dam. 1

Specific target organ toxicity - single exposure: STOT SE 3

Specific target organ toxicity - repeated exposure: STOT RE 2

Hazardous to the aquatic environment: Aquatic Chronic 3

Hazard Statements:

Highly flammable liquid and vapour.

Harmful if inhaled.

Causes skin irritation.

Causes serious eye damage.

May cause respiratory irritation.

May cause damage to organs through prolonged or repeated exposure.

Harmful to aquatic life with long lasting effects.

#### 2.2. Label elements

##### Regulation (EC) No. 1272/2008

##### Hazardous components for labelling

xylene

triacetoxymethylsilane

dioctyltin-di(acetate)

**Signal word:** Danger



## Product Name: Lacquer L nano

REF: 37511, 37512, 375130

Date of print: 20.04.2021 Date of last alteration: 20.04.2021

### Pictograms:



### Hazard statements

- H225 Highly flammable liquid and vapour.  
 H315 Causes skin irritation.  
 H318 Causes serious eye damage.  
 H332 Harmful if inhaled.  
 H335 May cause respiratory irritation.  
 H373 May cause damage to organs through prolonged or repeated exposure.  
 H412 Harmful to aquatic life with long lasting effects.

### Precautionary statements

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.  
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P310 Immediately call a POISON CENTER/doctor.  
 P370+P378 In case of fire: Use Carbon dioxide (CO<sub>2</sub>), Foam, Extinguishing powder to extinguish.  
 P403+P235 Store in a well-ventilated place. Keep cool.

### 2.3. Other hazards

No information available.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

#### Chemical characterization

Polydimethylsiloxane with functional groups in organic solvents.

#### Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
<b>1330-20-7</b>	<b>xylene</b>			<b>50 - &lt; 55 %</b>
	215-535-7	601-022-00-9	01-2119488216-32	
	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1, Aquatic Chronic 3; H226 H332 H312 H315 H319 H335 H373 H304 H412			
<b>108-87-2</b>	<b>methylcyclohexane</b>			<b>10 - &lt; 15 %</b>
	203-624-3	601-018-00-7		
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411			
<b>4253-34-3</b>	<b>triacetoxymethylsilane</b>			<b>1 - &lt; 5 %</b>
	224-221-9		01-2119962266-32	
	Acute Tox. 4, Skin Corr. 1C, Eye Dam. 1; H302 H314 H318 EUH014			



## Product Name: Lacquer L nano

REF: 37511, 37512, 375130

Date of print: 20.04.2021 Date of last alteration: 20.04.2021

17586-94-6	dioctyltin-di(acetate)			< 1 %
	241-555-0			

Full text of H and EUH phrases: see section 16.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

##### After inhalation

Provide fresh air. When in doubt or if symptoms are observed, get medical advice.

##### After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. Medical treatment necessary.

##### After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

##### After ingestion

Rinse mouth immediately and drink plenty of water. Seek immediately medical advice. Do not induce vomiting. In case of spontaneous vomiting take care of an unhindered flow out of the vomit ( danger of suffocation).

#### 4.2. Most important symptoms and effects, both acute and delayed

No information available.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

##### Suitable extinguishing media

Carbon dioxide (CO<sub>2</sub>), Foam, Extinguishing powder.

##### Unsuitable extinguishing media

Water.

#### 5.2. Special hazards arising from the substance or mixture

Highly flammable. Vapours can form explosive mixtures with air.

#### 5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit.

#### Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.



## Product Name: Lacquer L nano

REF: 37511, 37512, 375130

Date of print: 20.04.2021 Date of last alteration: 20.04.2021

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

#### 6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Explosion risk in case of fire.

#### 6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e. g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

#### 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

##### Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

##### Advice on protection against fire and explosion

Keep away from sources of ignition. - No smoking. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.

#### 7.2. Conditions for safe storage, including any incompatibilities

##### Requirements for storage rooms and vessels

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaustion at critical locations. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

##### Hints on joint storage

Do not store together with: Oxidising agent . Pyrophoric or self-heating substances. Oxidising agent Oxidising agent.

#### 7.3. Specific end use(s)

Liquid for coating of silicone based ear impressions. For use by trained specialist staff.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### Exposure limits (EH40)

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
1330-20-7	Xylene: mixed isomers	50	220		TWA (8 h)	WEL
		100	441		STEL (15 min)	WEL



## Product Name: Lacquer L nano

REF: 37511, 37512, 375130

Date of print: 20.04.2021 Date of last alteration: 20.04.2021

### Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value T	est material	Sampling time
1330-20-7	Xylene, o-, m-, p- or mixed isomers	methyl hippuric acid (creatinine)	650 mmol/mol	urine	Post shift

### 8.2. Exposure controls

#### Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

#### Protective and hygiene measures

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat, drink, smoke, sniff.

#### Eye/face protection

Suitable eye protection: goggles.

#### Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Suitable are gloves of the following material: FKM (fluoro rubber).

#### Skin protection

Flame-retardant protective clothing. Wear anti-static footwear and clothing.

#### Respiratory protection

In case of inadequate ventilation wear respiratory protection.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state: liquid

Colour: transparent, blue

Odour: Xylene/ Acetic acid

		Test method
pH-Value:	not determined	
<b>Changes in the physical state</b>		
Melting point:	not determined	
Initial boiling point and boiling range:	>99 °C	DIN 51356
Flash point:	<1 °C	DIN 51755
Sustaining combustion:	not sustaining combustion.	
<b>Flammability</b>		
Solid:	not applicable	
Gas:	not applicable	



## Product Name: Lacquer L nano

REF: 37511, 37512, 375130

Date of print: 20.04.2021 Date of last alteration: 20.04.2021

egger

<b>Explosive properties</b>	The product is not: Explosive.	
Lower explosion limits:	1.1 vol. %	
Upper explosion limits:	6.7 vol. %	
<b>Auto-ignition temperature</b>		
Solid:	not applicable	
Gas:	not applicable	
Decomposition temperature:	not determined	
<b>Oxidizing properties</b>	Not oxidizing.	
Vapour pressure (at 20 °C):	48 hPa	
Density (at 20 °C):	0.92 g/cm <sup>3</sup>	DIN 51757
Water solubility:	insoluble	
<b>Solubility in other solvents</b>	not determined	
Partition coefficient:	not determined	
Viscosity / dynamic (at 23 °C):	100 mPa·s	CP
Vapour density:	not determined	
Evaporation rate:	not determined	

### 9.2. Other information

Solid content: not determined

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Highly flammable.

### 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

### 10.3. Possibility of hazardous reactions

Reacts with: strong oxidising agents. The product may attack some plastic materials.

### 10.4. Conditions to avoid

Keep away from sources of heat (e. g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air. Therefore keep only in tightly closed containers between 15 °C/59 °F and 25 °C/77 °F.

### 10.5. Incompatible materials

No information available.

### 10.6. Hazardous decomposition products

The following applies for the silicone content of the product: At temperature of appr. 150 °C/302 °F a small amount of formaldehyde can be released by oxidative degradation.



## Product Name: Lacquer L nano

REF: 37511, 37512, 375130

Date of print: 20.04.2021 Date of last alteration: 20.04.2021

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

##### Acute toxicity

Harmful if inhaled.

##### ATEmix calculated

ATE (inhalation vapour) 18.94 mg/l; ATE (inhalation aerosol) 2.513 mg/l

CAS No	Chemical name				
	Exposure routes	Dose	Species	Source	Method
<b>1330-20-7</b>	<b>xylene</b>				
	oral	LD50 3500 mg/kg	Rat	GESTIS	
	dermal	LD50 >1700 mg/kg	Rabbit	GESTIS	
	inhalative (4 h) vapour	LC50 29.08 mg/l	Rat	GESTIS	
	inhalative aerosol	ATE 1.5 mg/l			
<b>108-87-2</b>	<b>methylcyclohexane</b>				
	oral	LD50 > 3200 mg/kg	Rat	GESTIS	
	dermal	LD50 86000 mg/kg	Rabbit		
<b>4253-34-3</b>	<b>triacetoxymethylsilane</b>				
	oral	LD50 1600 mg/kg	Rat	OECD 401	
<b>17586-94-6</b>	<b>dioctyltin-di(acetate)</b>				
	oral	LD50 >2000 mg/kg	Rat		
	inhalation vapour	ATE 0.5 mg/l			
	inhalation aerosol	ATE 0.05 mg/l			

##### Irritation and corrosivity

Causes skin irritation. Causes serious eye irritation.

##### Sensitising effects

Based on available data, the classification criteria are not met.

##### Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

##### STOT-single exposure

May cause respiratory irritation. (xylene)

##### STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure. (xylene)

##### Aspiration hazard

Based on available data, the classification criteria are not met.

##### Additional information on tests

This mixture is classified as hazardous according to regulation (EC) No. 1272/2008 [CLP].



## Product Name: Lacquer L nano

REF: 37511, 37512, 375130

Date of print: 20.04.2021 Date of last alteration: 20.04.2021

## SECTION 12: Ecological information

### 12.1. Toxicity

Harmful to aquatic life with long lasting effects.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
<b>1330-20-7</b>	<b>xylene</b>					
	Acute fish toxicity	LC50 2.661-4.093 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)		
	Acute crustacea toxicity	EC50 3.82 mg/l	48 h			
<b>108-87-2</b>	<b>methylcyclohexane</b>					
	Acute fish toxicity	LC50 58.5 mg/l	96 h		GESTIS	
	Acute crustacea toxicity	EC50 1.47 mg/l	48 h	Daphnia magna	ECOTOX	

### 12.2. Persistence and degradability

The product has not been tested.

### 12.3. Bioaccumulative potential

The product has not been tested.

### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
1330-20-7	xylene	3.15
108-87-2	methylcyclohexane	3.88

### BCF

CAS No	Chemical name	BCF	Species	Source
1330-20-7	xylene	0.6-15		

### 12.4. Mobility in soil

The product has not been tested.

### 12.5. Results of PBT and vPvB assessment

Not identified as PBT/ vPvB substances.

### 12.6. Other adverse effects

No information available.

### Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

#### Disposal recommendations

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.



## Product Name: Lacquer L nano

REF: 37511, 37512, 375130

Date of print: 20.04.2021 Date of last alteration: 20.04.2021

  
**egger**

### Contaminated packaging

@1301.B130039 Handle contaminated packages in the same way as the substance itself.

## SECTION 14: Transport information

### Land transport (ADR/RID)

**14.1. UN number:** UN 1866

**14.2. UN proper shipping name:** Resin solution

**14.3. Transport hazard class(es):** 3

**14.4. Packing group:** II

Hazard label: 3

Classification code: F1

Limited quantity: 5 L/30 kg

Hazard No: 33

Tunnel restriction code: D/E

### Other applicable information (land transport)

Flammable liquid

### Marine transport (IMDG)

**14.1. UN number:** UN 1866

**14.2. UN proper shipping name:** Resin solution

**14.3. Transport hazard class(es):** 3

**14.4. Packing group:** II

Hazard label: 3

Marine pollutant: -

Special Provisions: -

Limited quantity: 5 L/30 kg

EmS: F-E, S-E

### Other applicable information (marine transport)

Flash point: -4 °C c.c.

### Air transport (ICAO-TI/IATA-DGR)

**14.1. UN number:** UN 1866

**14.2. UN proper shipping name:** Resin solution

**14.3. Transport hazard class(es):** 3

**14.4. Packing group:** II

Hazard label: 3

Limited quantity Passenger: 1 L/30 kg

Passenger LQ: Y341

IATA-packing instructions - Passenger: 353

IATA-max. quantity - Passenger: 5 L

IATA-packing instructions - Cargo: 364

IATA-max. quantity - Cargo: 60 L

### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: yes

### 14.6. Special precautions for user

Warning: Combustible liquid.

**Product Name: Lacquer L nano**

REF: 37511, 37512, 375130

Date of print: 20.04.2021 Date of last alteration: 20.04.2021

**14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**

Not applicable.

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Information according to 2012/18/EU (SEVESO III): P5c FLAMMABLE LIQUIDS

**National regulatory information**

Employment restrictions: Observe restrictions to employment for juvenils according to the , juvenile work protection guideline' (94/33/EC).

Water contaminating class (D): 2 - obviously hazardous to water

**15.2. Chemical safety assessment**

Chemical safety assessments for substances in this mixture were not carried out.

**SECTION 16: Other information****Abbreviations and acronyms**ADR: Accord européen sur le transport des marchandises dangereuses par Route  
(European Agreement concerning the International Carriage of Dangerous Goods by Road )

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50 %

LD50: Lethal dose, 50 %

CLP: Classification, labelling and Packaging

REACH: Registration, Evaluation and Authorization of Chemicals

GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals

UN: United Nations

DNEL: Derived No Effect Level

DMEL: Derived Minimal Effect Level

PNEC: Predicted No Effect Concentration

ATE: Acute toxicity estimate

LL50: Lethal loading, 50%

EL50: Effect loading, 50%

EC50: Effective Concentration 50 %

ErC50: Effective Concentration 50 %, growth rate

NOEC: No Observed Effect Concentration

BCF: Bio-concentration factor

PBT: persistent, bioaccumulative, toxic

vPvB: very persistent, very bioaccumulative

RID: Regulations concerning the international carriage of dangerous goods by rail

EmS: Emergency Schedules

MFAG: Medical First Aid Guide

ICAO: International Civil Aviation Organization

MARPOL: International Convention for the Prevention of Marine Pollution from Ships



## Product Name: Lacquer L nano

REF: 37511, 37512, 375130

Date of print: 20.04.2021 Date of last alteration: 20.04.2021



egger

IBC: Intermediate Bulk Container  
 VOC: Volatile Organic Compounds  
 SVHC: Substance of Very High Concern  
 @1602.B016012

### Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Acute Tox. 4; H332	Calculation method
Skin Irrit. 2; H315	Calculation method
Eye Dam. 1; H318	Calculation method
STOT SE 3; H335	Calculation method
STOT RE 2; H373	Calculation method
Aquatic Chronic 2; H412	Calculation method

### Relevant H- and EUH-phrases (Number and full text)

H225 Highly flammable liquid and vapour.  
 H226 Flammable liquid and vapour.  
 H302 Harmful if swallowed.  
 H304 May be fatal if swallowed and enters airways.  
 H312 Harmful in contact with skin.  
 H314 Causes severe skin burns and eye damage.  
 H315 Causes skin irritation.  
 H318 Causes serious eye damage.  
 H319 Causes serious eye irritation.  
 H330 Fatal if inhaled.  
 H332 Harmful if inhaled.  
 H335 May cause respiratory irritation.  
 H336 May cause drowsiness or dizziness.  
 H371 May cause damage to organs.  
 H373 May cause damage to organs through prolonged or repeated exposure.  
 H411 Toxic to aquatic life with long lasting effects.  
 H412 Harmful to aquatic life with long lasting effects.  
 EUH014 Reacts violently with water.

### Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)