



Product Name: Lacquer L

REF: 37500, 37501, 37502, 37503, 37505, 37506, 3075030

Date of print: 21.04.2021 Date of last alteration: 21.04.2021



egger

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Lacquer L

UFI: 44TU-E913-A00E-8Y1C

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Silicone based lacquer for use in audiology.

1.3. Details of the supplier of the safety data sheet

Manufacturer/distributor: egger Otoplastik+Labortechnik GmbH

Street/POB-No.: Aybühlweg 59

Postal code/city/country: 87439 Kempten/Germany

Telephone: +49 831 58113-60

Telefax: +49 831 58113-14

Internet: www.egger.online

E-mail: sales@egger.online

1.4. Emergency telephone number: +49 89 19240

Emergency number: Munich, Germany, toxicological dep. of the II. Med. Hospital)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:

Flammable liquid: Flam. Liq. 2

Acute toxicity: Acute Tox. 4

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Dam. 1

Specific target organ toxicity - single exposure: STOT SE 3

Specific target organ toxicity - single exposure: STOT SE 3

Specific target organ toxicity - repeated exposure: STOT RE 2

Hazardous to the aquatic environment: Aquatic Chronic 2

Hazard Statements:

Highly flammable liquid and vapour.

Harmful if inhaled.

Causes skin irritation.

Causes serious eye damage.

May cause respiratory irritation.

May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

Toxic to aquatic life with long lasting effects.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

methylcyclohexane

xylene

triacetoxymethylsilane

dioctyltin-di(acetate)

**Product Name: Lacquer L**

REF: 37500, 37501, 37502, 37503, 37505, 37506, 3075030

Date of print: 21.04.2021 Date of last alteration: 21.04.2021


egger**Signal word:** Danger**Pictograms:****Hazard statements**

- H225 Highly flammable liquid and vapour.
 H315 Causes skin irritation.
 H318 Causes serious eye damage.
 H332 Harmful if inhaled.
 H335 May cause respiratory irritation.
 H336 May cause drowsiness or dizziness.
 H373 May cause damage to organs through prolonged or repeated exposure.
 H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P310 Immediately call a POISON CENTER/doctor.
 P370+P378 In case of fire: Use Carbon dioxide (CO₂), Foam, Extinguishing powder to extinguish.
 P403+P235 Store in a well-ventilated place. Keep cool.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Chemical characterization**

Polydimethylsiloxane with functional groups in organic solvents.

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
108-87-2	methylcyclohexane			30 - < 35 %
	203-624-3	601-018-00-7		
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411			
1330-20-7	xylene			30 - < 35 %
	215-535-7	601-022-00-9	01-2119488216-32	



Product Name: Lacquer L

REF: 37500, 37501, 37502, 37503, 37505, 37506, 3075030

Date of print: 21.04.2021 Date of last alteration: 21.04.2021

	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1, Aquatic Chronic 3; H226 H332 H312 H315 H319 H335 H373 H304 H412	
4253-34-3	triacetoxymethylsilane	1 - < 5 %
	224-221-9	01-2119962266-32
	Acute Tox. 4, Skin Corr. 1C, Eye Dam. 1; H302 H314 H318 EUH014	
17586-94-6	dioctyltin-di(acetate)	< 1 %
	241-555-0	
	Acute Tox. 2, Skin Corr. 1A, Eye Dam. 1, STOT SE 2; H330 H314 H318 H371	

Full text of H and EUH phrases: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

After inhalation

Provide fresh air. When in doubt or if symptoms are observed, get medical advice.

After contact with skin

After contact with skin, wash immediately with polyethylene glycol, followed by plenty of water. Take off immediately all contaminated clothing and wash it before reuse. Medical treatment necessary.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

After ingestion

Rinse mouth immediately and drink plenty of water. Seek immediately medical advice. Do not induce vomiting. In case of spontaneous vomiting take care of an unhindered flow out of the vomit (danger of suffocation).

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO₂), Foam, Extinguishing powder.

Unsuitable extinguishing media

Water.

5.2. Special hazards arising from the substance or mixture

Highly flammable. Vapours can form explosive mixtures with air.

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit.



Product Name: Lacquer L

REF: 37500, 37501, 37502, 37503, 37505, 37506, 3075030

Date of print: 21.04.2021 Date of last alteration: 21.04.2021


egger

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Danger of explosion.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e. g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Advice on protection against fire and explosion

Keep away from sources of ignition. - No smoking. Take precautionary measures against static discharges.

Vapours can form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaustion at critical locations. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints on joint storage

Do not store together with: Oxidising agent. Pyrophoric or self-heating substances.

7.3. Specific end use(s)

Liquid for coating of silicone based ear impressions.

For use by trained specialist staff.

**Product Name: Lacquer L**

REF: 37500, 37501, 37502, 37503, 37505, 37506, 3075030

Date of print: 21.04.2021 Date of last alteration: 21.04.2021

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
1330-20-7	Xylene: mixed isomers	50 100	220 441		TWA (8 h) STEL (15 min)	WEL WEL

Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
1330-20-7	Xylene, o-, m-, p- or mixed isomers	methyl hippuric acid (creatinine)	650 mmol/mol	urine	Post shift

8.2. Exposure controls**Appropriate engineering controls**

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Protective and hygiene measures

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

Eye/face protection

Suitable eye protection: goggles.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Suitable are gloves of the following material: FKM (fluoro rubber).

Skin protection

Flame-retardant protective clothing. Wear anti-static footwear and clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state: liquid

Colour: transparent

Odour: Xylene/ Acetic acid

		Test method
pH-Value:	not determined	
Changes in the physical state		
Melting point:	not determined	
Initial boiling point and boiling range:	>99 °C	DIN 51356



Product Name: Lacquer L

REF: 37500, 37501, 37502, 37503, 37505, 37506, 3075030

Date of print: 21.04.2021 Date of last alteration: 21.04.2021



egger

Flash point:	3 °C	DIN 1523
Sustaining combustion:	Not sustaining combustion.	
Flammability		
Solid:	not applicable	
Gas:	not applicable	
Lower explosion limits:	1.1 vol. %	
Upper explosion limits:	6.7 vol. %	
Auto-ignition temperature		
Solid:	not applicable	
Gas:	not applicable	
Decomposition temperature:	not determined	
Oxidizing properties	Not oxidizing.	
Vapour pressure (at 20 °C):	48 hPa	
Density (at 20 °C):	0.90 g/cm ³	DIN 51757
Water solubility:	insoluble	
Solubility in other solvents	not determined	
Partition coefficient:	not determined	
Viscosity / dynamic (at 23 °C):	100 mPa·s	CP
Vapour density:	not determined	
Evaporation rate:	not determined	

9.2. Other information

Solid content: not determined

SECTION 10: Stability and reactivity

10.1. Reactivity

Highly flammable.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Reacts with: strong oxidising agents. The product may attack some plastic materials.

10.4. Conditions to avoid

Keep away from sources of heat (e. g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

The following applies for the silicone content of the product: At temperature of appr. 150 °C/ 302 °F a small amount of formaldehyde can be released by oxidative degradation.



Product Name: Lacquer L

REF: 37500, 37501, 37502, 37503, 37505, 37506, 3075030

Date of print: 21.04.2021 Date of last alteration: 21.04.2021



SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Harmful if inhaled.

ATEmix calculated

ATE (inhalation aerosol) 4.068 mg/l

CAS No	Chemical name				
	Exposure routes	Dose	Species	Source	Method
108-87-2	methylcyclohexane				
	oral	LD50 > 3200 mg/kg	Rat	GESTIS	
	dermal	LD50 86000 mg/kg	Rabbit		
1330-20-7	xylene				
	oral	LD50 3500 mg/kg	Rat	GESTIS	
	dermal	LD50 >1700 mg/kg	Rabbit	GESTIS	
	inhalative (4 h) vapour	LC50 29.08 mg/l	Rat	GESTIS	
	inhalative aerosol	ATE 1.5 mg/l		GESTIS	
4253-34-3	triacetoxymethylsilane				
	oral	LD50 1600 mg/kg	Rat	OECD 401	
17586-94-6	dioctyltin-di(acetate)				
	oral	LD50 2000 mg/kg	Rat		
	inhalation vapour	ATE 0.5 mg/l			
	inhalation aerosol	ATE 0.05 mg/l			

Irritation and corrosivity

Causes skin irritation. Causes serious eye damage.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation. (xylene).

May cause drowsiness or dizziness. (methylcyclohexane).

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure. (xylene).

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

This mixture is classified as hazardous according to regulation (EC) No. 1272/2008 [CLP].



Product Name: Lacquer L

REF: 37500, 37501, 37502, 37503, 37505, 37506, 3075030

Date of print: 21.04.2021 Date of last alteration: 21.04.2021

SECTION 12: Ecological information

12.1. Toxicity

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
108-87-2	methylcyclohexane					
	Acute fish toxicity	LC50 58.5 mg/l	96 h		GESTIS	
	Acute crustacea toxicity	EC50 1.47 mg/l	48 h	Daphnia magna	ECOTOX	
1330-20-7	xylene					
	Acute fish toxicity	LC50 2.661-4.093 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)		
	Acute crustacea toxicity	EC50 3.82 mg/l	48 h			

12.2. Persistence and degradability

The product has not been tested.

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
108-87-2	methylcyclohexane	3.88
1330-20-7	xylene	3.15

BCF

CAS No	Chemical name	BCF	Species	Source
1330-20-7	xylene	0.6-15		

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

Not identified as PBT/ vPvB substances.

12.6. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

**Product Name: Lacquer L**

REF: 37500, 37501, 37502, 37503, 37505, 37506, 3075030

Date of print: 21.04.2021 Date of last alteration: 21.04.2021


egger**Contaminated packaging**

This material and its container must be disposed of as hazardous waste. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information**Land transport (ADR/RID)****14.1. UN number:** UN 1866**14.2. UN proper shipping name:** Resin solution**14.3. Transport hazard class(es):** 3**14.4. Packing group:** II

Hazard label: 3

Classification code: F1

Limited quantity: 5 L/30 kg

Hazard No: 33

Tunnel restriction code: D/E

Marine transport (IMDG)**14.1. UN number:** UN 1866**14.2. UN proper shipping name:** Resin solution**14.3. Transport hazard class(es):** 3**14.4. Packing group:** II

Hazard label: 3

Marine pollutant: yes

Special Provisions: -

Limited quantity: 5 L/30 kg

EmS: F-E, S-E

Other applicable information (marine transport)

Flash point: 3 °C c.c.

Air transport (ICAO-TI/IATA-DGR)**14.1. UN number:** UN 1866**14.2. UN proper shipping name:** Resin solution**14.3. Transport hazard class(es):** 3**14.4. Packing group:** II

Hazard label: 3

Limited quantity Passenger: 1 L/30 kg

Passenger LQ: Y341

IATA-packing instructions - Passenger: 353

IATA-max. quantity - Passenger: 5 L

IATA-packing instructions - Cargo: 364

IATA-max. quantity - Cargo: 60 L

Other applicable information (air transport)

Contains: methylcyclohexane, triacetoxymethylsilane

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: yes



Product Name: Lacquer L

REF: 37500, 37501, 37502, 37503, 37505, 37506, 3075030

Date of print: 21.04.2021 Date of last alteration: 21.04.2021



egger

14.6. Special precautions for user

Warning: Combustible liquid.

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 2 - obviously hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50 %

LD50: Lethal dose, 50 %

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Einstufung	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Acute Tox. 4; H332	Calculation method
Skin Irrit. 2; H315	Calculation method
Eye Dam. 1; H318	Calculation method
STOT SE 3; H335	Calculation method
STOT SE 3; H336	Calculation method
STOT RE 2; H373	Calculation method
Aquatic Chronic 2; H411	Calculation method

Relevant H- and EUH-phrases (Number and full text)

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.



Product Name: Lacquer L

REF: 37500, 37501, 37502, 37503, 37505, 37506, 3075030

Date of print: 21.04.2021 Date of last alteration: 21.04.2021



- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H330 Fatal if inhaled.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H371 May cause damage to organs.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H411 Toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.
- EUH014 Reacts violently with water.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)