



## Product Name: egger Acryl/B monomer

REF: 33500, 33501

Date of print: 04.09.2019 Date of last alteration: 17.07.2018

egger



### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

egger Acryl/B monomer

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### Use of the substance/mixture

Health services.

#### 1.3. Details of the supplier of the safety data sheet

Manufacturer/distributor: egger Otoplastik+Labortechnik GmbH

Street/POB-No.: Aybühlweg 59

Postal code/city/country: 87439 Kempten/Germany

Telephone: +49 831 58113-60

Telefax: +49 831 58113-14

Internet: www.egger-labor.com

E-mail: sales@egger-labor.de

#### 1.4. Emergency telephone number: +49 89 19240

Emergency number: Munich, Germany, toxicological dep. of the II. Med. Hospital)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Regulation (EC) No. 1272/2008

Hazard categories:

Flammable liquid: Flam. Liq. 2

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Respiratory or skin sensitisation: Skin Sens. 1

Specific target organ toxicity - single exposure: STOT SE 3

Hazard Statements:

Highly flammable liquid and vapour.

Causes skin irritation.

May cause an allergic skin reaction.

Causes serious eye irritation.

May cause respiratory irritation.

#### 2.2. Label elements

##### Regulation (EC) No. 1272/2008

##### Hazard components for labelling

methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate; methyl methacrylate

ethylene dimethacrylate

#### Signal word:

Danger

#### Pictograms:





# Product Name: egger Acryl/B monomer

REF: 33500, 33501

Date of print: 04.09.2019 Date of last alteration: 17.07.2018

## Hazard statements

H225 Highly flammable liquid and vapour.  
 H315 Causes skin irritation.  
 H317 May cause an allergic skin reaction.  
 H319 Causes serious eye irritation.  
 H335 May cause respiratory irritation.

## Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P280 Wear protective gloves/protective clothing/eye protection/face protection.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

#### Chemical characterization

methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate; methyl methacrylate

#### Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
<b>80-62-6</b>	<b>methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate; methyl methacrylate</b>			<b>&gt; 90 %</b>
	201-297-1	607-035-00-6		
	Flam. Liq. 2, STOT SE 3, Skin Irrit. 2, Skin Sens. 1; H225 H335 H315 H317			
<b>97-90-5</b>	<b>ethylene dimethacrylate</b>			<b>&lt; 10 %</b>
	202-617-2	607-114-00-5		
	STOT SE 3, Skin Sens. 1; H335 H317			
<b>3077-12-1</b>	<b>N,N-dihydroxyethylene-p-poluidine</b>			<b>&lt; 2 %</b>
	Acute Tox. 4, Eye Dam. 1; H302 H318			
<b>2440-22-4</b>	<b>2-(2H-Benzotriazol-2-yl)-p-cresol</b>			<b>&lt; 1 %</b>
	219-470-5			
	Skin Sens. 1B, Aquatic Chronic 1; H317 H410			

Full text of H and EUH statements: see section 16.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### After inhalation

Remove casualty to fresh air and keep warm and at rest. Medical treatment necessary.

#### After contact with skin

After contact with skin, wash immediately with: Water and soap. Subsequently wash off with: Polyethyleneglykol 400. Remove contaminated, saturated clothing immediately. Medical treatment necessary.



## Product Name: egger Acryl/B monomer

REF: 33500, 33501

Date of print: 04.09.2019 Date of last alteration: 17.07.2018



egger

### After contact with eyes

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

### After ingestion

If swallowed, immediately drink: Water. Caution if victim vomits: Risk of aspiration! Call a physician immediately.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### Suitable extinguishing media

Water spray. Carbon dioxide (CO<sub>2</sub>). Foam. Extinguishing powder.

#### Unsuitable extinguishing media

High power water jet.

### 5.2. Special hazards arising from the substance or mixture

Combustible. Vapours may form explosive mixtures with air.

### 5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

### Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Provide adequate ventilation. Do not breathe vapour. Avoid contact with skin, eyes and clothes. Wear personal protection equipment.

### 6.2. Environmental precautions

Do not allow to enter into surface water or drains. Explosion hazard.

### 6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e. g. sand, diatomaceous earth, acid- or universal binding agents). Take up mechanically. Treat the recovered material as prescribed in the section on waste disposal.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

#### Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe vapour. Vapours are heavier than air and will spread at floor level. Provide fresh air.

#### Advice on protection against fire and explosion

Keep away from sources of ignition. - No smoking. Use explosion-proof machinery, apparatus, ventilation facilities, tools etc. Use only non-sparking tools.



## Product Name: egger Acryl/B monomer

REF: 33500, 33501

Date of print: 04.09.2019 Date of last alteration: 17.07.2018

  
egger

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from sources of ignition. - No smoking. Keep/Store only in original container. Protect against: Light.

#### Advice on storage compatibility

Do not store together with: Material, rich in oxygen, oxidizing.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Exposure limits (EH40)

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
80-62-6	Methyl methacrylate	50	208		TWA (8 h)	WEL
		100	416		STEL (15 min)	WEL

### 8.2. Exposure controls

#### Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe vapour.

#### Protective and hygiene measures

Remove contaminated, saturated clothing immediately. Protect skin by using skin protective cream. After work, wash hands and face. When using do not eat or drink. Avoid contact with eyes and skin. Separate storage of work clothes.

#### Eye/face protection

Wear eye/face protection.

#### Hand protection

Recommendation:

Dermatril Single-use gloves. NBR (Nitrile rubber). 0,11 mm penetration time (maximum wearing period): 0 min.

REF 162-907-00 (7/S), REF 162-908-00 (8/M), REF 162-909-00 (9/L)

Camapren 720, CR (polychloroprenes, Chloroprene rubber). 0,65 mm penetration time (maximum wearing period): > 10 min, KCL

#### Respiratory protection

Do not breathe vapour.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state: liquid

Colour: clear

Odour: like: ester



## Product Name: egger Acryl/B monomer

REF: 33500, 33501

Date of print: 04.09.2019 Date of last alteration: 17.07.2018

		Test method
<b>Changes in the physical state</b>		
Melting point:	-48 °C	
Initial boiling point and boiling range:	100.3 °C	
Flash point:	10 °C	DIN 51755
Lower explosion limits:	2,1 vol. %	
Upper explosion limits:	12,5 vol. %	
Ignition temperature:	430 °C	DIN 51794
Vapour pressure: (at 20 °C)	40 hPa	
Density (at 20 °C):	0,94 g/cm <sup>3</sup>	
Water solubility: 15,9 g/L (at 20 °C)	15,9 g/L	
<b>Solubility in other solvents</b>		
	miscible with most organic solvents	
Partition coefficient:	Distribution coefficient (n-octanol / water) (log P O/W): 0,7	
Viscosity / dynamic: (at 20 °C)	Brookfield 0,6 mPa·s	

### 9.2. Other information

Relative vapour density at 20 °C (air=1): &gt; 1

## SECTION 10: Stability and reactivity

### 10.3. Possibility of hazardous reactions

Reacts with : Reducing agents. Heavy metals. Peroxides. Radical former.  
In case of warming: Polymerization.

### 10.4. Conditions to avoid

Keep away from heat. Ignition hazard.

### 10.6. Hazardous decomposition products

none

### Further information

Thermal decomposition: at room temperature none

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### Acute toxicity

Acute toxicity (inhalant): 7093 ppm 4h

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
80-62-6	<b>methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate; methyl methacrylate</b>				
	oral	LD50 > 5000 mg/kg	Rat		
	dermal	LD50 > 5000 mg/kg	Rabbit		



## Product Name: egger Acryl/B monomer

REF: 33500, 33501

Date of print: 04.09.2019 Date of last alteration: 17.07.2018

<b>3077-12-1</b>	<b>N,N-dihydroxyethylene-p-poluidine</b>					
	oral	LD50	300 mg/kg	@N11.P000002	OECD 401	

### Irritation and corrosivity

Irritant effect on the skin: Not an irritant. 24h

Irritant effect on the eye: Not an irritant.

Following inhalation: Lung irritation. Coughing. Shortage of breath.

### Sensitising effects

May cause sensitization by inhalation and skin contact.

### Carcinogenic/mutagenic/toxic effects for reproduction

Longterm experiments do not indicate carcinogenic effects . No experimental indications of mutagenicity in-vitro exist.

### Additional information on tests

The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

## SECTION 12: Ecological information

### 12.1. Toxicity

Algae toxicity:EC50: 37 mg/L 8d

Bacterial toxicity: Pseudomonas putida 100 mg/L

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
<b>80-62-6</b>	<b>methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate; methyl methacrylate</b>					
	Acute fish toxicity	LC50	> 79 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)	
	Acute crustacea toxicity	EC50	69 mg/l	48 h	Daphnia magna	
<b>97-90-5</b>	<b>ethylene dimethacrylate</b>					
	Acute fish toxicity	LC50	15,95 mg/l	96 h	Brachydanio rerio (zebra-fish)	
	Acute crustacea toxicity	EC50	44,9 mg/l	48 h	Daphnia magna	

### 12.2. Persistence and degradability

Not easily bio-degradable (according to OECD-criteria).

### Further information

Do not allow to enter into surface water or drains.

The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

#### Advice on disposal

Send to a hazardous waste incinerator facility under observation of official regulations.



## Product Name: egger Acryl/B monomer

REF: 33500, 33501

Date of print: 04.09.2019 Date of last alteration: 17.07.2018

egger

### Waste disposal number of used product

140603 WASTE ORGANIC SOLVENTS, REFRIGERANTS AND PROPELLANTS (EXCEPT 07 AND 08); waste organic solvents, refrigerants and foam/aerosol propellants; other solvents and solvent mixtures; hazardous waste

### Contaminated packaging

Water (with cleaning agent). Completely emptied packages can be recycled.

## SECTION 14: Transport information

### Land transport (ADR/RID)

14.1. UN number: UN 1247

14.2. UN proper shipping name: METHYL METHACRYLATE MONOMER, STABILIZED

14.3. Transport hazard class(es): 3

14.4. Packing group: II

Hazard label: 3



Classification code: F1

Limited quantity: 1 L

Excepted quantity: E2

Transport category: 2

Hazard No: 339

Tunnel restriction code: D/E

### Marine transport (IMDG)

14.1. UN number: UN 1247

14.2. UN proper shipping name: METHYL METHACRYLATE MONOMER, STABILIZED

14.3. Transport hazard class(es): 3

14.4. Packing group: II

Hazard label: 3



Special Provisions: -

Limited quantity: 1 L

Excepted quantity: E2

EmS: F-E, S-D

### Air transport (ICAO)

14.1. UN number: UN 1247

14.2. UN proper shipping name: METHYL METHACRYLATE MONOMER, STABILIZED



## Product Name: egger Acryl/B monomer

REF: 33500, 33501

Date of print: 04.09.2019 Date of last alteration: 17.07.2018



egger

**14.3. Transport hazard class(es):** 3

**14.4. Packing group:** II

Hazard label: 3



Special Provisions: A209

Limited quantity Passenger: 1 L

Passenger LQ: Y341

Excepted quantity: E2

IATA-packing instructions - Passenger: 353

IATA-max. quantity - Passenger: 5 L

IATA-packing instructions - Cargo: 364

IATA-max. quantity - Cargo: 60 L

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: no

## SECTION 15: Regulatory information

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**National regulatory information**

Water contaminating class (D): 1 - slightly water contaminating

## SECTION 16: Other information

### Changes

This data sheet contains changes from the previous version in section(s): 1, 3, 7, 9.

### Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.

H302 Harmful if swallowed.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H410 Very toxic to aquatic life with long lasting effects.

### Further Information

@N16.P0000001

@N16.P0000002

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)