



Effective suction by vacuum pump



Sonic-Brush for perfect cleansing



Blue LED light for illumination



Easy handling by only one tactile button



Rechargeable by LiPo battery



Mobility by USB-C standard



3 intensity levels for flexible application



All features controlled by microprocessor



Highest product quality with 2 year warranty



Energy-efficient, gentle and absolutely safe

PRODUCT DESCRIPTION

The vac-clean uv 2[®] is a powerful mini vacuum cleaner with different attachment nozzles. A LED illumination and rechargeable battery extend the range of applications. All types of hearing aids and consumer electronics can be cleaned with the various attachment nozzles and combined vacuum.

IDENTIFICATION

Product name: vac-clean uv 2[®]
REF: 62100000
 WEEE-Reg. no.: DE 47525015

 flow-med GmbH
 Weinbergweg 10
 73773 Aichwald
 Germany

TECHNICAL DATA

Vacuum: Vacuum high performance diaphragm pump with -60kPa (8.7 psi).
 Air flow 1.7 l/min, noise level < 50dB(A)

Power modes: 3 suction levels (ooo / oo / o) with different strengths,
 Touch sensor button briefly to turn on, maximum suction power is default (mode ooo),
 Switch between the suction levels by briefly touching the sensor button

Switch off: Manual by touching and holding the sensor button for 3 seconds

LED light: 1 blue LED illuminates the working area for better visibility

Operation: Via built-in Li-polymer battery 1.100 mAh,
 USB-C cable included, operation during charging is possible

Safety: Input voltage monitoring at <4V and >6V

LiPo battery: Lithium polymer battery model 102540, 3.7V, 1.100mAh, UN3481, charging time approx. 2.5 hours

Operating time: Max. 2.5 hours full load operation, which corresponds to 37 working cycles of 4 minutes each

Stand-by: Stand-by power <0.001W

PACKAGING CONTENT

1 vac-clean uv 2[®] in hardcover etui, 1 Instruction for use
 1 USB-cable (USB-A to USB-C) 1.0 m
 1 Replacement-Set 2 including 1x base attachment,
 2x Silicone sealing ring, various heads (2x Brush, 2x Ear,
 2x Tube, 1x S-Tube, 1x RIC, 1x Skin, 1x Oval)

ENERGY SUPPLY

No USB power supply included
 LiPo battery can be charged or operated at any
 USB output or USB power supply (5V / 1A, DC)
 Operation during charging is possible

WARRANTY

2 Years from production date **LOT**

LABEL



DIMENSIONS, WEIGHT AND UDI-DI

Device:	130 mm x 47 mm x 33 mm (L x W x H)	207 g	UDI-DI
1 pcs product carton:	170 mm x 105 mm x 52 mm (L x W x H)	336 g	4260277013240
10 pcs shipping carton:	565 mm x 185 mm x 135 mm (L x W x H)	3,700 g	4260277013257
20 pcs shipping carton:	590 mm x 390 mm x 170 mm (L x W x H)	8,200 g	4260277013264